



MOUNTING BRACKET, UG-MB

For mounting of duct smoke detector, Uniguard Superflow, on circular or insulated flat ducts.



VENTURI PIPE, VR-xM

- VR-0.6M Venturi pipe 0.6 meter to UG-3
- VR-1.5M Venturi pipe 1.5 meter to UG-3
- VR-2.8M Venturi pipe 2.8 meter to UG-3

For ducts smaller than 0,6 m use venturi pipe length 0,6 m.
 For ducts between 0,6 and 1,3 m use venturi pipe length 1,5 m.
 For ducts over 1,4 m use venturi pipe length 2,8 m.



EXTENSION TUBE FOR VENTURI TUBES, ST-EXTEND

ST-EXTEND is an extension tube to existing standard tubes and compatible with other venturi tubes from the VR and ST series. A number of extension tubes can be assembled together and replace both the 1.5 m and 2.8 m tubes in our range. Length 1.06 m.



LED INDICATION, LED-03

For showing the location of a hidden smoke detector, giving an alarm. For 24V-systems. Maximal cable length 3 m.



Height 280 mm
 Width Ø 282 mm

PROTECTION COVER, UG-COVER

UG-COVER is used as a condensation protection for Uniguard Superflow smoke detector, installed outdoors or in cold attics.